



Rust Converter

Product Description

VHT® Rust Converter destroys rust on contact. It sprays on clear and turns to a black metal-protecting coating to prevent future rust from forming. Specifically formulated for application over metal, body filler or fiberglass. It sands to a smooth even finish.

Product Characteristics

Color: Black

Finish: Flat

Properties

Product Weight: 6.34 lb/gal

Flash Point: Propellant < 0° F

Coating System

VHT provides a multi-high performance coating system for the ultimate in protection and quality. The system includes surface preparation and rust converter.

Prep Mild Soap

Coat SP229 Rust Converter

Uses

Provides protective coating for the ultimate protection and quality against rust.

Surfaces:

- Metal, Body Filler, or Fiberglass.

Application

Prepare a surface by removing loose paint, dirt, rust, grease, wax, etc. Remove as much rust and scale as possible using 50 grit sand paper or wire brush. Wash with mild soap and water. Rinse well and dry with clean cloth.

Mask-off surrounding areas to protect from overspray. Use at temperatures 60° F (16° C) 95° F (35° C) and when humidity is less than 60%.

Shake can vigorously for one full minute and 10 seconds after each minute of use. To spray, hold can parallel 8 to 10 inches from the surface to be coated and use in an even, sweeping motion. To avoid runs and sags, apply 2-3 light coats, allowing surface to dry no more than 2 minutes between coats. Final application should dry to a black finish. Protect from moisture and allow surface to dry 24 hours before applying topcoat. If needed, dry sanding can be done to achieve a smooth coat before applying primer or topcoat. Covers approximately 12 to 14 square feet.

No curing necessary.

Packaging

Fill Weight: 10.36 oz

Per Case: 6 cans

Case Weight: 5.51 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans